

SILVYN® KLICK-RH

SILVYN® KLICK-RH - conduit holder for SILVYN® RILL

Info

One-piece conduit holder



Assembly time



Temperature-resistant

Benefits

- Fast assembly
- Easy to disassemble
- High tensile strength
- Conduit retained by rib
- No loose parts

Application range

In combination with protective conduit
SILVYN® RILL PA 6
SILVYN® RILL PA 12
Fastening of conduits on machine walls for all applications

Product features

- Impact-resistant polyamide
- One-piece conduit holder
- Suitable for mounting onto a C-profile rail
- Stackable

Product Make-up

One-piece conduit holder with M5/M6 borehole for fixation

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC001171

ETIM 5.0 Class-Description: Holder for protective hose

Last Update (15.09.2020)

©2020 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® KCLICK-RH

| | |
|------------------------|---|
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC001171 ETIM 6.0 Class-Description: Holder for protective hose |
| Colour delivered: | Grey (RAL 7031) Black (RAL 9011), UV-resistant |
| Material: | PA6 Halogen-free |
| Temperature range: | -40 °C to +115 °C |

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

SILVYN® KLICK-RH

| Article number | Nominal size | Hole Ø (mm) | Suitable for SILVYN® RILL | Pieces / PU |
|------------------------|--------------|-------------|---------------------------|-------------|
| SILVYN® KLICK-RH grey | | | | |
| 65500630 | 10 | 5 | 10 | 50 |
| 65500631 | 13 | 5 | 13 | 50 |
| 65500632 | 16 | 6 | 16 | 50 |
| 65500633 | 18 | 6 | 18 | 50 |
| 65500634 | 21 | 6 | 21 | 50 |
| 65500635 | 28 | 6 | 28 | 25 |
| 65500636 | 34 | 6 | 34 | 25 |
| 65500637 | 42 | 6 | 42 | 25 |
| 65500638 | 54 | 6 | 54 | 10 |
| SILVYN® KLICK-RH black | | | | |
| 65500639 | 10 | 5 | 10 | 50 |
| 65500640 | 13 | 5 | 13 | 50 |
| 65500641 | 16 | 6 | 16 | 50 |
| 65500642 | 18 | 6 | 18 | 50 |
| 65500643 | 21 | 6 | 21 | 50 |
| 65500644 | 28 | 6 | 28 | 25 |
| 65500645 | 34 | 6 | 34 | 25 |
| 65500646 | 42 | 6 | 42 | 25 |
| 65500647 | 54 | 6 | 54 | 10 |

Last Update (15.09.2020)

©2020 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03.16