HELIX[®] CHARGING CABLE

ITEM NO.: 5555935013 | TYPE 2, MODE 3, 20A, 3-phase, 5m FOR CHARGING ELECTRIC AND HYBRID CARS

THE HELIX® CHARGING CABLE FROM LAPP with 5m extension length allows easy and fast charging at public charging stations and wallboxes. The HELIX® makes it easier for users to handle the cable when charging their vehicle. Thanks to its shape memory, the cable automatically reverts to its original shape after charging. Vehicles can be charged with up to 20A 3-phase. The high protection rating of IP55, together with the additional longitudinal waterproofing, ensures excellent moisture protection. The charging cable, which is designed in accordance to the applicable IEC and EN standards, is both robust and durable, but also easy to handle thanks

INCLUDED IN DELIVERY

to its low weight.

- Charging cable for public charging stations and wall boxes
- Manual

APPLICABLE STANDARDS

- EC 61851-1
- IEC 62893-1
- EN 61851-1
- EN 50620
- EN 17186
- 2014/35/EU (Low Voltage Directive)
- 2011/65/EU (RoHS), 215/863/EU

TECHNICAL DATA

- Item no.: 5555935013
- Connections:
- Type 2 on both sides • Charging mode:
- Mode 3 according to IEC 62196
- Rated current: 20A
- Rated voltage: 440V AC 3-phase
- Max. Charging power: 11kW

- Permissible temperature range: -40°C +50°C
- Cable type: ÖLFLEX[®] CHARGE Helix 5G2.5+0.5
- Extension length: 5.0 meters
- Protection class IP55 with additional longitudinal watertightness
- Halogen free
- Flame retardant
- Oil resistant

Lapp Mobility GmbH Oskar-Lapp-Str. 2 · D-70565 Stuttgart · Tel.: +49 711 7838 - 04 Fax: +49 711 7838 - 3520 · www.lappmobility.com

