

Polyamide-Fitting N


Metr., PG NPT



Material	Polyamide
Protection category	IP54 with CRing with fixed conduit mounting IP65
Operating Temperature	-20°C - +80°C (-4°F - +176°F)
Colours	grey (RAL 7031), black (RAL 9005)



// protection against unintended disconnct. Use screwdriver to disassemble



AG	D mm	GL mm	H mm	mm	fits to Polyamide-Conduit DN	Number grey	Number black
M16x1,5	20	8	23	17	10	1.511.1600.50	1.511.1601.50
M20x1,5	26,5	9	28	24	14	1.511.2000.50	1.511.2001.50
M25x1,5	38,5	11	32	35	23	1.511.2500.50	1.511.2501.50
M32x1,5	46	11	35	42	29	1.511.3200.50	1.511.3201.50
FG9	19	8	23	17	10	1.511.0900.14	1.511.0901.14
FG11	23	8	25	21	12	1.511.1100.14	1.511.1101.14
FG13,5	26,5	9	28	24	14	1.511.1300.14	1.511.1301.14
FG16	30	10	29	27	17	1.511.1600.14	1.511.1601.14
FG21	38,5	11	32	35	23	1.511.2100.14	1.511.2101.14
FG29	46	11	35	42	29	1.511.2900.14	1.511.2901.14
FG36	54,5	13	41	50	37	1.511.3600.14	1.511.3601.14
FG48	70	14	46	64	50	1.511.4800.14	1.511.4801.14
NPT 3/8"	19	15	23	17	10	1.511.3800.70	1.511.3801.70
NPT 1/2"	30	13	29	27	17	1.511.1216.70	1.511.1217.70
NPT 3/4"	38,5	13	32	35	23	1.511.3400.70	1.511.3401.70
NPT 1"	46	15	35	42	29	1.511.1000.70	1.511.1001.70